



## EPIC™ STANDARD COLORS

WILFLEX™ Epic Standard Colors are specifically formulated for high productivity wet-on-wet printing. The Epic Standard Colors are semi-opaque and the Epic Super Standard Colors are boosted with extra opacity. These colors have excellent resistance to build-up and may also be used to print conventional cold-peel transfers.

### HIGHLIGHTS

- Popular industry colors, ready for use saving time to mix
- Wet-on-wet printing at high production speeds with exceptional resistance to build-up
- Translucent to semi-opaque colors
- Satin finish
- Good color fastness to crocking test

### PRINTING TIPS

- Use consistent, high-tensioned screen mesh and sharp edged squeegees for best print results
- Colors vary in opacity from translucent to semi-opaque
- Exhibits good color reproduction on white garment and over a base plate. For some colors, base mixing systems are limited in color saturation and may require an increased ink deposit or formula adjustment to achieve accurate color
- EPIC Standard Colors is not a low-bleed ink; when printing on fabrics that are prone to bleed underbase with an approved WILFLEX low bleed white and/or blocker
- Exhibits good color retention in high-speed wet-on-wet production with exceptional resistance to build up
- Adjust flash cure temperature and dwell time so ink is just dry to touch. Depending on flash unit, a 2 - 3 second flash is adequate
- For cold-peel transfers, use a coated release paper or polyester film

### COMPLIANCE

- Non-phthalate
- For individual compliance certifications and conformity statements, please visit: [www.avient.com/wilflex-compliance](http://www.avient.com/wilflex-compliance)

### PRECAUTIONS

The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications




AVIENT  
SPECIALTY  
INKS

V3.04 (Modified: 07/19/2022)

## PRODUCT INFORMATION BULLETIN



### RECOMMENDED PARAMETERS



#### Fabric Types

100% cotton, cotton blends, some synthetics



#### Mesh

Count: 86-230 t/in (34-91 t/cm)  
Tension: 25-35 n/cm<sup>2</sup>




#### Squeegee

Durometer: 60/90/60, 70/90/70, 60-90  
Profile: Square, Sharp  
Stroke: Medium flood, Medium-Fast stroke  
Angle: 10-15%



#### Stencil

2 over 2  
Off Contact: 1/16" (.2cm)  
Emulsion Over Mesh: 15-20%



#### Flash & Cure

Flash: 220°F (105°C)  
Cure: 320F (160C)



#### Pigment Loading

N/A



#### Wilflex™ Additives

ASI K2910 VISCOSITY BUSTER-1% max  
ASI K2920 FINESSE



#### Storage

65-90°F (18-32°C)  
Avoid direct sunlight  
Use within one year of receipt



#### Clean Up

Ink degradant or press wash



#### Health & Safety

Find SDS information here:  
[www.avient.com/resources/safety-data-sheets](http://www.avient.com/resources/safety-data-sheets)  
or contact your local CSR