



Union Ink™ Stellar White Ink Series

The Union Ink™ Stellar White Ink Series is developed to give you the best white ink for your printing needs. Whether you are printing on 100% Cotton or Poly/Cotton Blends, these Stellar White Inks are designed for easy printing, excellent opacity, soft feel, and maximum bleed resistance.

PADE1040 LUNAR COTTON WHITE is an easy printing, high-opacity white ink with excellent coverage on dark garments. The low tack formula allows printing through finer mesh counts without needing a viscosity modifier. Use as an underlay where good opacity is needed, a stand-alone white, or as a highlight white.

PLHE1060 ECLIPSE LOW BLEED WHITE is a high-opacity, low tack formulation that allows printing through finer mesh counts without needing a viscosity modifier. PLHE1060 has good low bleed characteristics for printing on poly/cotton blends. Use as an underlay where excellent opacity is needed, a stand-alone white, or as a highlight white.

PLHE1050 MERCURY LOW BLEED WHITE is created for maximum smoothness and opacity on poly/cotton fabrics. Mercury LB White has excellent matting characteristics and a creamy consistency. PLHE1050 is fast flashing, allowing for shorter dwell times and faster production rates. This low bleed white ink is great for both manual and automatic presses. Use as a highlight, a stand-alone, or underlay white.

GLOBAL COMPLIANCE

Union Ink™ is certified to ZDHC Conformance Level 3 with ECO PASSPORT by OEKO-TEX®. To learn more about compliance standards, please contact your Avient Specialty Inks distributor.



1.844.4AVIENT
www.avient.com



Copyright © 2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.