

LFP901 LFP-901 BLACK



LFP inks print well through a full range of meshes.

Highlights

- Versatile and ready to use.

Printing Tips

- LFP inks print well through screen meshes in the range of 83-305 t/in (32-120 t/cm).
- Screens stretched to a minimum of 25 newtons are recommended.
- If using lower tension screens, adjust off contact accordingly. Use just enough squeegee pressure to deposit the ink on the surface of the shirt.
- A 70, 80 or 70/90/70 durometer sharp squeegee is recommended.
- All LFP inks are ready to use. They can be extended using K2915 CURABLE REDUCER. Opacity may be affected.












Compliance

- Internationally compliant
- Non-phthalate
- <https://www.avientspecialtyinks.com/services/compliance-support>

Precautions

- The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications.

Recommended Parameters

 Fabric Types Cotton	 Flash & Cure Flash: 140-150°F on pre-heated pallets Cure: 60 seconds at 325°F	 Clean Up Standard plastisol cleaners, press wash, or ink degradant
 Mesh Count: 86-305 t/in Tension: 25n/cm3	 Pigment Loading Not recommended	 Health & Safety Find SDS information here: www.avient.com/resources/safety-data-sheets or contact your local CSR
 Squeegee Durometer: 70, 80, or 70/90/70 Profile: Square Stroke: X1 Stroke, Medium speed Angle: 5-15%	 Additives K2915 CURABLE REDUCER	<p>2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.</p>
 Stencil Standard Emulsion Off Contact: 1/16" (2mm) or greater Emulsion Over Mesh: 15-20%	 Storage 65 -95° F (18 -35 C) Avoid direct sunlight. Use within one year of receipt. Keep container well sealed.	
	AVIENT SPECIALTY INKS	V1.10 (Modified: 08/18/2023)