

## » RUTLAND™ CHILL™ LB FLEXIBLE CURE READY-FOR-USE INKS

Rutland™ Chill™ flexible cure inks are ready-for-use screen printing inks that cure as low as 250°F (121°C) and up to 320°F (160°C). This series consists of 24 bright, easy-to-print colors for cotton and 17 high-opaque colors for polyester.

**Note:** Chill™ LC (low cure) colors are ready-for-use colors for cotton. Chill LB colors are low-bleed colors for polyester.



LC/LB 0730  
Gray

LC/LB 1212  
Violet

LC/LB 2402  
Lite Navy

LC/LB 2406  
Dark Navy

LC/LB 2584  
Royal

LC/LB 2589  
Lite Blue

LC/LB 2768  
Bright Blue

LC 3034  
Fluor Green

LC/LB 3399  
Forest Green

LC/LB 3403  
Dallas Green

LC/LB 4202  
Gold

LC 4038  
Fluor Yellow

LC/LB 4215  
Yellow RS

LC/LB 4611  
Yellow

LC/LB 4769  
Bright Gold

LC 5019  
Fluor Orange

LC/LB 5202  
Orange

LC 6058  
Fluor Red

LC 7495  
Spice Brown

LC 7574  
Dark Brown

LC/LB 6279  
Red

LC/LB 6398  
Cardinal

LC/LB 6400  
Scarlet

LC 8033  
Black

Color Chips: The color chips presented on this color card are simulations of Rutland colors. Slight variations may be seen between these chips and actual Rutland inks. Printed results may vary based on production methods such as ink film thickness, opacity, and substrate.



For more information about Rutland flexible cure inks, visit [www.avientspecialtyinks.com](http://www.avientspecialtyinks.com)



1.844.4AVIENT  
[www.avient.com](http://www.avient.com)



Copyright © 2025, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.