



MagnaPrint® Pearl Flex Neutral

Ready to print pearlescent stretchy pastes

MagnaPrint® Pearl Flex Neutral is a ready to use stretchy / flexible print paste containing speciality pigments to obtain a “metallic like” effect.

MagnaPrint® Pearl Flex Neutral has excellent elasticity properties and can be printed directly onto the fabric to achieve fantastic stretch and durability without the need for a under base

MagnaPrint® Pearl Flex Neutral can be pigmented with the addition of up to 6% Eco Pigments to give desired shade.

Application

MagnaPrint® Pearl Flex Neutral should be printed through a 32-61 (86 -156) mesh screens with rectangular profile squeegees.

As the particle size is 10-60 micron this should be considered when selecting screen mesh.

When printing as part of a multi coloured design print the MagnaPrint® Pearl Flex Neutral as the last screen to avoid pick up.

After printing the garment/panel should be cured, ideally for 2½ -3 minutes @165°C (330°F).

Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

SPECIFICATION



FABRIC TYPES
Cotton / Poly Cotton
Blends



MESH
32 - 61T (86 - 156) Mesh



SQUEEGEE
Medium 65 Shore Rectangular



STENCIL
Water resistant emulsion



CURE TEMPERATURE
2-2½ Minutes at 165°C (330°F)



PIGMENT LOADING
Up to 6% MagnaPrint® Eco
Pigments



ADDITIVES
Retardant Gel Conc, Crosslinker
100, Softener TS Conc



STORAGE
In cool place properly
closed: >5c (40F) <25c (77F)



HEALTH & SAFETY
MSDS available upon
request



CLEAN UP
Wash off screen using water
and mild detergent

