



MagnaTrans™ Adhesive 60

Printable Adhesive

MagnaTrans™ Adhesive 60 is a printable adhesive for use with the MagnaTrans range. Offering strong adhesion and a 60° C washfastness when applied to fabrics.

Application

Ensure your transfer print is completely dry before applying adhesive.

MagnaTrans Adhesive 60 is applied as the final layer to the finished transfer using 34 – 55T (86-140) screen mesh, with a 60-65° Medium Shore Rectangular Squeegee.

Once applied, cure the transfer for 1-1.5 minutes at 140°C - 160°C (285°F - 320°F).

The finished transfer can be applied to the required substrate on a heat press at 165°C (329°F) for 12 seconds, 6 Bar pressure.

Once pressed, remove the transfer film from the print.

SPECIFICATION



FABRIC TYPES

Cotton, Poly-Cotton Blends, Polyester*



MESH

34 – 55T (86 - 140)



SQUEEGEE

60-65° Medium Shore, Rectangular Squeegee



CURE TEMPERATURE

1-1.5 minutes at 140°C - 160°C (285°F - 320°F)



STORAGE

In cool place properly closed: >5°C (40°F) <25°C (77°F)



HEALTH & SAFETY

MSDS available upon request



CLEAN UP

Wash off screen using water and mild detergent

* With the use of MagnaTrans Migration Blocker.

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.

Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

